

Spectrol API SM Passenger Car Crankcase Oils

Description:

- Spectrol API SM Passenger Car Crankcase Oils are performance oils formulated for gasoline and light-diesel engines.
- Spectrol API SM Passenger Car Crankcase Oils are manufactured using highly refined paraffinic base oils and select additives to provide superior thermal and oxidative stability, corrosion and valve train-wear protection, and will prevent the formation and accumulation of deposits and sludge.

Typical Applications:

- Spectrol Passenger Car Crankcase Oil is acceptable for use in passenger cars, and light-duty trucks and may be recommended for the following uses: SM, SL, SJ, SH, SG, SF, SE, SD or SC oils.

Typical Physical Properties:

<u>Viscosity Grade</u>	<u>SAE 10W-40</u>	<u>SAE 20W-50</u>
Density, lb/gal @ 60°F 60°F (15.6°C)	7.26 0.8703	7.21 0.8653
Viscosity, @ 40°C, cSt	88.7	151
Viscosity, @ 100°C, cSt	13.7	18.4
Viscosity Index	159	141
Flash Point (PMCC), °C	>170 °C	>170 °C
Pour Point (D97), °C	-33	-21
Zn (ppm)	853	853
P (ppm)	746	746
Ca (ppm)	1952	1952
CCS Viscosity ,cP	6500 (-25 °C)	9110 (-15 °C)
Noack Volatility @250C	12.8	10